

## Cudy FS1016D 16-Port 10/100M Base-TX Port Switch

Šifra: 63278  
Kategorija proizvoda: SVIČEVI  
Proizvođač: cudy

Cena: **3.470,00** rsd.



- 16 x 10/100Mbps Auto-Negotiation RJ45 ports supporting Auto-MDI/MDIX
- Comply with IEEE 802.3, IEEE 802.3u, IEEE802.3x standards
- Supports MAC address auto-learning and auto-aging
- Supports IEEE802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode
- Plug & Play, Desktop design

Plug and play, hassle-free, no configuring is required.

Auto MDI/MDIX eliminates the need for crossover cables.

Auto-negotiation on each port detects the link speed of a network device (10/100Mbps) and intelligently adjusts for compatibility and optimal performance.

### High Performance

Auto-negotiation RJ-45 ports can provide large file transferring and also be compatible with any 10/100Mbps Ethernet devices. Featuring non-blocking switching architecture, the product forwards and filters packets at full wire-speed for maximum throughput.

IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode offer increased bandwidth to alleviate network congestion, making the switch work reliably.

### 10/100Mbps Ports for Faster Speed

Increase the speed of your network with the 16-port switch. Non-blocking, 16 10/100Mbps ports enables instant transferring of large, bandwidth intensive files without interference.

### Smooth Online Experience

The switch connects up to 16 devices with a speed of up to 100Mbps (Half Duplex)/200Mbps (Full Duplex). Provides you with an extremely smooth experience to enjoy a powerful, seamless, affordable and easy-to-use network, ideal for multimedia, graphics, HD video and other applications that require large transfer allocation.

### Energy Efficient and Power Saving

Automatically adjusts Power consumption according to the link status and cable length. This Gigabit Desktop Switch features the innovative energy-efficient technologies that can greatly expand your network capacity with much less power.

Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3x

Protocol: CSMA/CD

Data Rate: Ethernet: 10Mbps (Half Duplex)/20Mbps (Full Duplex) Fast Ethernet: 100Mbps (Half Duplex)/200Mbps (Full Duplex)

Transmission Method: Store-and-Forward

Switching Features: MAC address auto-learning and auto-aging Half and Full Duplex 1.6Gbps backplane bandwidth

Interfaces: 16 x 10/100Base-TX Port

LED Indicators: LAN~LAN16, Power

MAC Address Table: 2K entries per device

Power Supply: DC 5V 1A

Dimensions W\*D\*H: 138mm x 103mm x 35 mm

Weight: 0.228kg

Operating Temperatur: 0°C~40°C (32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Relative Humidity: 10%~90%, non-condensing

Storage Humidity: 5%~95%, non-condensing

Package Contents: 1 x Power Adapter;1 x Switch;1 x User Manual